

01-27-00

A

01/24/00
JCS11 U.S. PTO

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE

**UTILITY PATENT APPLICATION
TRANSMITTAL LETTER
UNDER 37 C.F.R. 1.53(b)**

ATTORNEY DOCKET NO.:

10191/1294

JCS11 U.S. PTO
09/489618

01/24/00

Address to:

Assistant Commissioner for Patents
Washington D.C. 20231
Box Patent Application

Transmitted herewith for filing is a patent application.

Inventor(s): Erich HERMANN, Hartmut BAESSLER, Uwe KLEINSCHMIDT and Burkhard TRIESS

For: **A METHOD AND A DEVICE FOR CHECKING THE FUNCTIONING OF A COMPUTER**

1. Enclosed are:

- ☒ 2 sheet(s) of drawing(s).
- ☐ A certified copy of German Appln. 1 99 03 302.1 filed on January 28, 1999 on which priority is based.
- ☐ Assignment of the invention to Robert Bosch GmbH.
- ☒ A declaration/power of attorney. (Unsigned)
- ☐ An Information Disclosure Statement and an accompanying PTO-1449.

Other: _____

2. The filing fee has been calculated as shown below:

	NUMBER FILED	NUMBER EXTRA*	RATE (\$)	FEE (\$)
BASIC FEE				690.00
TOTAL CLAIMS	8 - 20=	0	18.00	0.00
INDEPENDENT CLAIMS	2 - 3=	0	78.00	0.00
MULTIPLE DEPENDENT CLAIM PRESENT			260.00	
*Number extra must be zero or larger			TOTAL	690.00
If the applicant is a small entity under 37 C.F.R. §§ 1.9 and 1.27, then divide total fee by 2, and enter amount here.			SMALL ENTITY TOTAL	

EM360464137US

Please charge the required application filing fee of **\$690.00** to the deposit account of **Kenyon & Kenyon**, deposit account number **11-0600**.

3. The Commissioner is hereby authorized to charge payment of the following fees, associated with this communication or arising during the pendency of this application, or to credit any overpayment, to the deposit account of **Kenyon & Kenyon**, deposit account number **11-0600**:
- A. Any additional filing fees required under 37 C.F.R. § 1.16;
 - B. Any additional patent application processing fees under 37 C.F.R. § 1.17;
 - C. Any additional document supply fees under 37 C.F.R. § 1.19;
 - D. Any additional post-patent processing fees under 37 C.F.R. § 1.20; or
 - E. Any additional miscellaneous fees under 37 C.F.R. § 1.21.
4. A duplicate copy of this letter is enclosed for that purpose.

Respectfully submitted,

Dated: 1/27/00

By: 

Richard L. Mayer
Reg. No. 22,490

KENYON & KENYON
One Broadway
New York, New York 10004
(212) 425-7200 (telephone)
(212) 425-5288 (facsimile)

A METHOD AND A DEVICE FOR CHECKING THE FUNCTIONING OF A COMPUTER

Background Information

It is already known for the purpose of checking the functioning of a computer to divert the access from the normal working (main) memory of the computer to an alternate memory. In this alternate memory, other program flows or other data for the program flows can then be used, and a check test can therefore be carried out as to whether the computer then better monitors (registers) its open-loop and closed-loop control functions. Furthermore, so-called debuggers are known which generate statements concerning the internal operating states of the computer. Checking of this type was only possible in the laboratory but not under the near-series conditions of the computer.

Summary Of The Invention

The method and the device of the present invention have the advantage that it is possible to check the functioning of the computer under real operating conditions. In this context, both the functioning of existing programs as well as the effects of alterations of programs on the functioning of the computer can be analyzed.

It is particularly advantageous to obtain information concerning the states of the registers or ports arranged in the computer. By integrating the analysis program into the normal operating system, it can be assured that important functions can still be monitored by the computer. Thus it is assured that even when applications are running, no disruptions of the essential open-loop or closed-loop control functions of the computer occur as a result of the analysis.

Brief Description Of The Drawings

Figure 1 shows a schematic view of a computer, a working memory, and an alternate memory.

Figure 2 shows a more detailed view of the alternate memory.

EM360464137US

Figure 3 elaborates on a further exemplary embodiment of the present invention based on the assumption that the computer has read-only access to the working memory.

Detailed Description

- 5 In Figure 1, a computer (microcontroller) 1 is depicted during the checking of its functioning. Microcomputer 1, in a normal operating state, is connected to a working memory 2 via bus lines 5. Bus lines 5 are designed both for the exchange of addresses as well as for the exchange of data (address and data bus). Working memory 2 has a program area 3 and a data area 4. During normal operation, computer 1 processes a program that is contained in the program memory area 3 and for this purpose uses the data that is stored in data area 4. For the purpose of checking the functioning of computer 1, provision is made for a changeover switch 6. By activating changeover switch 6, computer 1 is connected via bus lines 5 to alternate memory 10 and no longer to working memory 2. Alternate memory 10 has an alternate program area 11, an alternate data area 12, and an auxiliary program area 13. As indicated by bus lines 50 arranged in Figure 1 to the left of alternate memory 10, alternate memory 10 not only has the capacity to exchange information with computer 1, but it also can be written into or read out from, from the outside.
- 10
- 15
- 20 Alternatively, it is also possible that changeover switch 6 only changes one part of working memory over to an alternate memory. For example, it would be possible only to change program area 3 over to alternate program area 11, while data area 4 would be used by computer 1 as before.
- 25
- 30 Alternate memory 10 has the property that it can be written into and the memory content can be read out from the outside. This makes it possible to check the mode of functioning of computer 1 and the functioning of selected program parts or data areas. For this purpose, in alternate memory 10, for example in alternate program area 11 or in alternate data area 12, information is written-in that differs from the information in program area 3 and in data area 4, respectively. Computer 1, for example, can be an open-loop control for an internal combustion engine. For these open-loop control tasks,

certain closed-loop control programs are stored in the program area, and in data area 4 performance data is stored that is specific to the engine in question and that is used by the closed-loop control programs. In order to improve the open-loop control of the engine for test purposes, altered closed-loop control programs and altered performance data are written into alternate memory 10, and the check test is thus carried out as to whether the altered closed-loop control or open-loop control programs and the altered performance data bring about an improved functioning of computer 1 or of the functions under the open-loop control of computer 1. In this context, it is of particular interest for the checking of new closed-loop or open-loop control programs to investigate the mode of operation or functioning of computer 1 in certain extreme operating states. For this purpose, it must be possible to check the internal operating states of computer 1. Checking of this type is not necessary in the normal operation of computer 1. Therefore, for alternate memory 10 provision is made for an auxiliary program area 13, in which appropriate auxiliary programs are stored which make possible a checking of this type of the functioning and mode of operation of computer 1.

The mode of functioning of this auxiliary program is further explained on the basis of Figure 2. In Figure 2, once again alternate memory 10 having alternate program area 11, alternate data area 12, and auxiliary program area 13 is depicted in detail.

Alternate memory 10 is configured, for example, as a so-called dual port RAM, in which, in addition to computer 1, access may be had to alternate memory 10 from the outside. Auxiliary program 13 contains various areas having various functions. Program area 101 is an analysis program, which is executed by computer 1 and which functions to analyze the operating states of computer 1. Furthermore, provision is made for an auxiliary program memory area 102, which functions to store data for the analysis program.

Analysis program 101 (i.e., the program that is stored in area 101) is designed to analyze internal states of computer 1. For this purpose, analysis program 101, for example, has the capacity to cause computer 1 to read out the state of individual internal registers, ports, or other memory areas that cannot be read out directly from the

outside. This takes place by analysis program 101 causing computer 1 to give the data stored in a certain register to the data bus and to indicate on the address bus an address that is found in auxiliary program memory area 102. In this way, the state of the register in question is written into auxiliary program memory area 102. The state of this register arranged in computer 1 can then be analyzed by reading out from the outside the appropriate memory locations in auxiliary program memory area 102. Furthermore, auxiliary program memory area 102 can also be used to communicate to the analysis program which registers, ports, and the like of computer 1 are to be analyzed. For this purpose, instructions are to be written in from outside into a preselected area of auxiliary program memory area 102, which cause analysis program 101 to investigate the corresponding areas of computer 1.

For activating auxiliary program 13, provision is to be made for the possibility that computer 1 leaves normal program 11 and is prompted to process auxiliary program 13. For example, this can occur by making provision in alternate program area 11 for an operating system that from time to time checks to determine whether there is a request from the outside to process auxiliary program 13. A request of this type could, for example, be written into auxiliary program memory area 102. In this case, the operating system contains a query loop, which checks to determine whether there is a corresponding instruction at the corresponding location of auxiliary program memory area 102. If a corresponding instruction exists, analysis program 101 is then activated.

A further possibility is depicted in Figure 2, in which a jump instruction 100 to analysis program 101 is provided from outside at a predetermined memory location 100 in the normal program flow provided for in alternate program area 11. This jump instruction, if necessary, is written in from outside into alternate memory 10. In addition to an unconditional jump instruction, for example, interrupt instructions or the like are also conceivable. By writing a jump instruction of this type into memory location 100, whenever the program located at the corresponding location in alternate program area 11 is called up, analysis program 101 is processed instead of this program.

If the checking of computer 1 takes place during the ongoing operation of computer 1, then care should be taken that at least the most important control functions executed by computer 1 are not disturbed as a result of the checking of the functioning of computer 1. However, this is usually not a problem in modern computers, since, in addition to the

actual control functions, they monitor another series of subsidiary functions, which can also be omitted from time to time without resulting in a substantial impairment of the system to be controlled. If computer 1, for example, is provided for controlling the engine functioning of a gasoline engine, then, for example, the processing of program parts concerned with the injection of fuel and with ignition should not be disturbed.

These functions are processed by computer 1 with precedence over all other functions. Additionally, however, provision is made for further programs, for example, programs that collect various data on the operating states of the engine and transmit them for checking functions. In this context, it is assured by an operating system that the essential control functions are constantly monitored, whereas the less important control or analysis functions of the engine are only monitored when no important control functions are taking place. Analysis program 101 should only be activated if no important control functions have to be processed by computer 1. As already indicated, this can be done by including a jump instruction 100 in a less important program part. Normally, the various functions that the programs monitor are realized by various program modules, and it is assured by an operating system (however it is executed), that the modules that are relevant for important control functions are also more often called up, i.e., are processed by the computer. The jump instruction should be written into a less important module in order, during ongoing operation of the computer, to be able still to monitor the important control functions.

A further possibility is generated by the fact that the operating system in alternate program area 11 regularly queries as to whether the activation of analysis program 101 is desired by a user and only permits this to happen if no important control functions have to be monitored by computer 1. This manner of proceeding also makes it possible to investigate the operating state of computer 1 during the ongoing control function. Thus, under real operating conditions using the real hardware of computer 1,

statements can be generated concerning the operating states of computer 1, the execution of a particular program inside computer 1, or concerning the relationship of the internal states of the processor and the closed-loop and open-loop control functions carried out by the computer.

5

There are computers 1 which allow access to their working memory 2 that is only read-out but not write-in. A computer of this type and the means necessary for checking a computer of this type are depicted in Figure 3. Reference numerals 1 through 6 and 10 through 13 again designate the same objects as were described in Figure 1.

10

In contrast to Figure 1, however, in Figure 3, read line 30 and write line 31 of computer 1 are depicted. Using a signal on read line 30, computer 1 signals to the memory chips that a reading access is now operative. This takes place such that the memory units, in response to the signal on line 30, give to the data bus the memory content of the memory location that is indicated on the address bus. Using a signal on write line 31, the memory chips are signaled that there is now a writing access, i.e., the memory chips write the data that are located on the data bus into the memory chips having the address that is on the address bus.

15

20

As can be seen in Figure 3, working memory 2 and alternate memory 10 are only connected to computer 1 by a read line 30, i.e., the programs or data can only be read-out from these memory units. Furthermore, there is one additional memory chip 41, which is connected to computer 1 both by read line 30 as well as by write line 31. The computer 1 can therefore both write as well as read out data in memory 41. Memory chip 41, of course, is also connected to computer 1 by bus lines 5.

25

Computer 1, working memory 2, and memory 41 constitute a control device, as can be used, for example, for the control of gasoline engines. Memory 41, to which computer 1 has both writing as well as reading access, makes it possible for computer 1 to temporarily store data. For checking the functioning of computer 1, provision is made for a further memory 42, which is connected to computer 1 by data lines 5 and write line

30

31. However, from outside, access can be had to memory 42 that is both writing as well as reading. This is indicated by bus lines 50 below memory chip 42 in Figure 3.

Memory chip 42 is now arranged by its address area so that its addressable area
 5 completely overlaps with the addressable area of memory 41. However, provision can additionally be made that memory chip 42 is larger than memory 41 and therefore has an additional addressable area. By reading out data in memory 42, information concerning the memory content of memory 41 and additional information can also be read out. Since in every write instruction, as a result of the overlapping address areas,
 10 all the data that is written into memory 41 by computer 1 is also simultaneously written into memory 42, by reading out the memory content of memory 42, it can therefore be determined how the memory content of memory 41 looks.

Furthermore, memory 42 can be used to transport results of analysis program 101 to
 15 the outside. For this purpose, the analysis program provides that the content of certain internal registers, ports, etc. of computer 1 is given to the data bus, a write instruction simultaneously being generated and an address being given to the address bus, the address being located in the addressable area of memory 42. To the extent that no other programs can have access to the corresponding memory locations, this data is
 20 also located in an address area in which memory 41 is addressable. However, if writing this data in memory 41 is to be avoided, for example because memory 41 is entirely needed for the normal operation of computer 1, then the data can be stored in additional address areas of memory 42, in which memory 41 is not addressable.

25 The reason for the somewhat complicated design in Figure 3 is due to the fact that the checking of the functioning of computer 1 requires an intervention in the hardware of a corresponding control unit. It is therefore often not possible, as needed, to contact the write or read line present in principle in the computer. Rather, one is usually required to use the lines that are provided as a matter of course for the special hardware design.
 30 Since for the normal operation of a control unit having a computer 1 it is sufficient if only a reading access is possible to working memory 2 and provision is only made for a

small memory 41 relative to memory 2, access to memory 41 being possible in both reading and writing modes, a corresponding device for checking the functioning of a computer 1 in a control device of this type must be adapted to the hardware accordingly.

What Is Claimed Is:

1. A method for checking a functioning of a computer, the computer, in a normal operating state, accessing a working memory using bus lines, a content of the working memory being able to be influenced by a user, the method comprising the steps of:
 - diverting an access of the computer, by a switchover device, such that the access is directed to an alternate memory rather than to the working memory; and
 - executing an auxiliary program in the alternate memory when activated by the computer, the auxiliary program making available information concerning internal operating states of the computer.
2. The method according to claim 1, further comprising the step of posing a query in the auxiliary program as to which information is of interest to the user.
3. The method according to claim 1, wherein the auxiliary program contains program steps that cause the computer to give a content of internal registers and ports to a bus using a write instruction for a certain address.
4. The method according to claim 3, further comprising the step of reading out, by the user, a memory in an address area.
5. The method according to claim 1, further comprising the step of executing an instruction in an alternate program area for causing the computer to begin processing an analysis program and for activating the auxiliary program.
6. The method according to claim 5, wherein the alternate program memory contains a first program module and a second program module of greater importance than the first program module, and further comprising the step of writing the instruction into the first program module.
7. The method according to claim 1, further comprising the steps of:
 - using an operating system, generating a query as to whether an analysis

of the computer should be undertaken; and

using the operating system, activating an analysis program if the query is answered affirmatively.

8. A device for checking a functioning of a computer, comprising:



a readable alternate memory including an auxiliary memory area, the auxiliary memory area containing an analysis program, the analysis program, when activated, supplying information concerning internal states of the computer; and


means for redirecting a connection of the computer from a working memory to the alternate memory.

Abstract Of The Disclosure

A method and a device for checking the functioning of a computer are proposed, the computer in a normal operating state having access to the working memory via bus lines. For the purposes of checking, provision is made for an alternate memory and a switchover device, as a result of the switchover device the access of the computer being diverted such that access is not to the working memory but rather to the alternate memory. The content of the alternate memory can be influenced by a user. In the alternate memory provision is made for an auxiliary program, which is executed when activated by the computer and which makes available information concerning the internal operating states of the computer.

250356



**Fig. 3**

**COMBINED DECLARATION AND
POWER OF ATTORNEY FOR PATENT APPLICATION**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below adjacent to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **A METHOD AND A DEVICE FOR CHECKING THE FUNCTIONING OF A COMPUTER**, and the specification of which:

- ☒ is attached hereto;
- ☐ was filed as United States Application Serial No. _____ on _____, 19__ and was amended by the Preliminary Amendment filed on _____, 19__.
- ☐ was filed as PCT International Application Number _____ on the ____ day of June, 19__.
- ☐ an English translation of which is filed herewith.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a). I hereby claim foreign priority benefits under Title 35, United States Code § 119 of any foreign application(s) for patent or inventor's certificate or of any PCT international applications(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a

EM360464137US.

filing date before that of the application(s) of which priority is claimed:

**PRIOR FOREIGN/PCT APPLICATION(S)
AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. § 119**

Country : Germany

Application No. : 1 99 03 302.1

Date of Filing: January 28, 1999

Priority Claimed

Under 35 U.S.C. § 119 : ☒ Yes ☐ No

I hereby claim the benefit under Title 35, United States Code § 120 of any United States Application or PCT International Application designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations § 1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

**PRIOR U.S. APPLICATIONS OR
PCT INTERNATIONAL APPLICATIONS
DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. § 120**

U.S. APPLICATIONS

Number :

Filing Date :

**PCT APPLICATIONS
DESIGNATING THE U.S.**

PCT Number :

PCT Filing Date :

I hereby appoint the following attorney(s) and/or agents to prosecute the above-identified application and transact all business in the Patent and Trademark Office connected therewith.

(List name(s) and registration number(s)):

Richard L. Mayer,	Reg. No. 22,490
Gerard A. Messina,	Reg. No. 35,952
_____	Reg. No. _____
_____	Reg. No. _____

All correspondence should be sent to:

Richard L. Mayer, Esq.
Kenyon & Kenyon
One Broadway
New York, New York 10004

Telephone No.: (212) 425-7200
Facsimile No.: (212) 425-5288

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment or both under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full name of inventor Erich HERMANN

Inventor's signature _____ Date _____

Citizenship Federal Republic of Germany

Residence Zuegelstr. 41
70806 Kornwestheim
Federal Republic of Germany

Post Office Address Same as above

Full name of inventor Hartmut BAESSLER

Inventor's signature _____ Date _____

Citizenship Federal Republic of Germany

Residence Hoelderlinstr. 7
73663 Berglen
Federal Republic of Germany

Post Office Address Same as above

Full name of inventor Uwe KLEINSCHMIDT

Inventor's signature _____ Date _____

Citizenship Federal Republic of Germany

Residence Waiblinger Weg 10
 71732 Tamm
 Federal Republic of Germany

Post Office Address Same as above

Full name of inventor Burkhard TRIESS

Inventor's signature _____ Date _____

Citizenship Federal Republic of Germany

Residence Balinger Str. 38
 71636 Ludwigsburg
 Federal Republic of Germany

Post Office Address Same as above